

# DATASHEET

## ER-3910M8GE-IPS



### Products Unique.

In addition to the most famous brands, we are specialized in providing solutions with alternative products to impress customers and competitors. Customized. The flexibility of our vendors, allows us to get out of the box to find the perfect cut on the needs of the customer.



ER TLC srl

Our Offer

Planning

Analyzing the demand, we help the customer to find the best solution.

Supplying

We evaluate the most suitable products for each situation, assisting the customer in choosing the best way.

Post Sales

We follow the customer throughout the life of the product, to always be a guarantee of quality.

We offer solutions for every kind of connectivity

- © Copper
- © Fiber
- © Wireless



SILVER SPONSOR



Member of CISQ Federation



# ER-3910M8GE-IPS

## FEATURES:

- 8\*10/100/1000M + 2\*1000M SFP fiber Port Industrial PoE Switch, 1-8 ports support IEEE 802.3af/at;
- PoE port support AF/AT intelligent recognition. Standard power is 15.4W/port, Maximum power: 30W/port;
- Only support 1,2(+)/3,6(-);
- Support L2+ full network management, PoE network management and configuration;
- Switching capacity: 192Gbps, MAC table: 8K;
- Input voltage: DC48-57V, Redundant dual power 5-bit industrial terminals;
- IP protection level: IP40; Rail-type installation

## INTRODUCTION:

The ER-3910M8GE-IPS is a full Gigabit managed industrial PoE switch. It has 8\*10/100/1000M PoE ports and 2\*100/1000 SFP fiber slot ports, port 1-8 can support IEEE 802.3af/at standard POE power supply, single port POE power up to 30W, and the maximum POE output power is 120W (at-240W). As a POE power supply device, it can automatically detect and identify the electrical equipment that meets the standard and supply power through the cable. It can supply the POE terminal equipment, such as wireless AP, network camera, network telephone, industrial sensor and so on, to meet the demand for high density PoE power supply network environment. It is suitable for intelligent transportation, rail transportation, electric power industry, mining, metallurgy and green energy construction and so on. A reliable communication networks. Managed model supports a variety of network redundancy protocol STP/RSTP/MSTP (<50ms). When one-way network fails, communication can be recovered quickly to ensure uninterrupted communication of important applications. ER-3910M8GE-IPS industrial series products fully follow industrial product design and material. The shell adopts aluminum alloy to enhance heat dissipation efficiency, IP40 protection grade, and ensures the stable operation of the equipment in bad environment. According to the actual application needs, through Web, CLI, SNMP network management, POE power supply management, port flow control, VLAN division, STP, RSTP and other functions of the application service configuration.



Pagina: 1 di 7



Model	ER-3910M8GE-IPS
Interface	8*10/100/1000Base-TX PoE ports (Data/Power) 2*10/100/1000M SFP slot (Data) 1 * RS232 console port (115200, N,8,1) 2 set of V+, V- redundant DC power interface (5 Pin Phoenix terminal)
PoE Port	Port 1-8 supports POE @ IEEE802.3af/at
Network Protocol	IEEE802.3 10BASE-T; IEEE802.3i 10Base-T; IEEE802.3u 100Base-TX; IEEE802.3ab 1000Base-T; IEEE802.3z 1000Base-X; IEEE802.3x
PoE Standard	IEEE802.3af/at
Ethernet Port Feature	10/100/1000BaseT (X) automatic detection, full / half duplex MDI/MDI-X adaptive
SFP Port Characteristic	Gigabit SFP optical fiber interface, default matching optical modules, need to buy separately, (optional order mode / multi-mode, single fiber / double fiber optical module.
Forwarding Mode	Store and Forward (Full Wire Speed)
Switching Capacity	192bps (Non-blocking)
Forwarding Rate@ 64byte	14.88Mpps
MAC	8K
Buffer Memory	4M
Jumbo Frame	10K
Twisted Pair Transmission	10BASE-T: Cat3,4,5 UTP (≤100 meter) 100BASE-TX: Cat5 or later UTP (≤100 meter) 1000BASE-T: Cat5e or later UTP (≤100 meter)
Optical Cable	Multimode: 850nm 0 ~ 500M; Single mode: 1310nm 0 ~ 40KM, 1550nm 0 ~ 120KM.
Power Supply Pin	Only support 1/2 (+), 3/6 (-) 4-core power supply



Working Voltage	48-57VDC; 5 Pin industrial Phoenix terminal, support anti-reverse protection.
Max Power Per Port	30W; IEEE802.3af/at
Total PWR / Input Voltage	Input Voltage:12V-40V; Output Voltage:48V ; 12V Booster.
Power Consumption	Standby:<10W; Full load:<240W
LED Indicator	System indicator: SYS (green); Network Indicator: Link (yellow); SFP Indicator: L/A (green); PoE Indicator: PoE (green)
Power Supply	No, optional 48V/120W or 48V/240W industrial power supply
Operation TEMP / Humidity	-40~+75°C;5%~90% RH Non condensing
Storage TEMP /	-40~+85°C;5%~95% RH Non condensing

Humidity	
Dimension	165*120*52mm
Net /Gross Weight	<0.8kg / <1.2kg
Lightning protection / protection level	Lightning protection: 6KV 8/20us; Protection level: IP40 IEC61000-4-2(ESD): ±8kV contact discharge, ±15kV air discharge IEC61000-4-3(RS):10V/m(80~1000MHz) IEC61000-4-4(EFT): power cable: ±4kV; data cable: ±2kV IEC61000-4-5(Surge): power cable:CM±4kV/DM±2kV; data cable: ±4kV IEC61000-4-6(radio frequency transmission):10V(150kHz~80MHz) IEC61000-4-8(power frequency magnetic field):100A/m;1000A/m ,1s to 3s IEC61000-4-9(pulsed magnet field):1000A/m IEC61000-4-10(damped oscillation):30A/m 1MHz IEC61000-4-12/18(shockwave):CM 2.5kV, DM 1kV IEC61000-4-16(common-mode transmission):30V; 300V,1s FCC Part 15/CISPR22(EN55022): Class B IEC61000-6-2(Common Industrial Standard)
Mechanical Properties	IEC60068-2-6 (anti vibration) IEC60068-2-27 (anti shock) IEC60068-2-32 (free fall)



Certification	CCC; CE mark, commercial; CE/LVD EN60950; FCC Part 15 Class B; RoHS;
Warranty	5 years, lifelong maintenance.
<b>Business features (only restricted management function models)</b>	
Port	Support IEEE802.3x flow control (full duplex) Support for broadcast storm suppression based on port rate support speed limit for incoming and offline message traffic, with a minimum particle size of 64Kbps. Support port temperature protection settings Support port EEE green Ethernet energy saving configuration
PoE Management	Support total power limit configuration for POE power supply Support PoE output power allocation per port, close / start af/at Support PoE output priority configuration per port Support PoE work status per port display Support power delay start Support PoE work and time scheduling
Layer 3 Function	L2+ network management function Support IPV4/IPV6 management Support layer3 soft routing (weak three tier) forwarding, Support different network segments, communication between different VLAN Support static routing / default routing 128, 1024 ARP software forwarding
VLAN	Support port based VLAN (4K), IEEE802.1q
	Support protocol based VLAN Support Voice VLAN Support for MAC address-based VLANs Support Access, Trunk, Hybrid three types of port configuration Support QinQ configuration



Port Aggregation	Support LACP Support static polymerization Support the largest 8 aggregation groups, each aggregation group supports 8 ports.
Spanning Tree	Support STP (IEEE802.1d) Support RSTP (IEEE802.1w) Support MSTP (IEEE802.1s)
Industrial Ring Network Protocol	Support G.8032 (ERPS), support 255 loops at most, and supports 1024 devices per ring. The self-healing time of the ring network is less than 20ms
Multicast	Support IGMP Snooping V1/V2 and support 1024 multicast groups at most. Support the user's quick departure mechanism Support MLD Snooping V1/V2 Support multicast VLAN
Mirror	Bi-directional traffic mirroring supporting the basic port

QoS	<p>Support Diff-Serv QoS</p> <p>Each port supports 8 output queues</p> <p>Support 802.1p/DSCP priority mapping</p>
	<p>Support queue scheduling mechanism (SP, WRR, SP+WRR)</p> <p>Support priority tag Mark/Remark</p> <p>Support stream-based packet filtering</p> <p>Support for stream-based redirection Support flow-based speed limit</p>
ACL	<p>Support L2 to L4 packet filtering function, can match the first 80 bytes of the message, provide based on the source MAC address, destination MAC address, source IP address, destination IP address, IP protocol type, TCP/UDP port, TCP/UDP port range, VLAN and other definition ACL.</p> <p>Support ACL based on port and VLAN</p>
Safety Characteristics	<p>Support user grading management and password protection</p> <p>Support IEEE802.1X authentication / centralized MAC address authentication</p> <p>Support AAA&amp;RADIUS authentication</p> <p>Support the number of MAC address learning restrictions Support MAC address black hole</p> <p>Support SSH 2.0 to provide secure passwords for user login.</p> <p>Support SSL to ensure data transmission security</p> <p>Support port isolation</p> <p>Support the speed limit function of ARP message</p> <p>Support IP source address protection</p> <p>Support ARP intrusion detection function</p> <p>Support against DoS attacks</p> <p>Support port broadcast message suppression</p>
	<p>Support host data backup mechanism Binding capabilities of IP+MAC+VLAN+ ports</p>
DHCP	<p>Support DHCP Client</p> <p>Support DHCP Snooping</p> <p>Support DHCP Server</p> <p>Support DHCP Relay</p>



Management and Maintenance	Support Console/AUX Modem/Telnet/SSH2.0 CLI command line configuration Support WEB network management (HTTPS) Support FTP, TFTP, Xmodem, SFTP file download management Support SNMP V1/V2C/V3 Support one bond reduction Support NTP clock Support system work log Support Ping detection Support cable state detection Support CPU instant utilization status view
----------------------------	--

